



PLASTICS AUTOMATION



Single-phase loaders

## FK KASKO

- ▶ Silent  $\leq 76$  dB(A)
- ▶ Soft start
- ▶ Discharging valve with gasket

Kasko single-phase is a sturdy machine suitable for the most demanding applications. Kasko's uniqueness is due to a clean design, stainless steel construction, and the attention to details. Completely made in Italy with first quality materials it's a product without any compromise. **Low noise  $\leq 76$  dB(A)** as per legal deadlines allows to install Kasko in the working place. Kasko F is prearranged for the installation of the proportional valve. It doesn't need any maintenance thanks to the automatic filter cleaning system.

*Kasko single-phase è una macchina robusta adatta ai lavori più gravosi, il design è pulito, la costruzione inox e l'attenzione al dettaglio la rendono unica nel suo genere. Prodotta in Italia con materiali di prima qualità, non contiene compromessi. La **bassa rumorosità  $\leq 76$  dB(A)** rientra nei termini di legge e può essere installata in ambienti di lavoro. KASKO F è predisposto per accettare la valvola proporzionale. Dotato di pulizia automatica del filtro, non necessita di manutenzione.*

$\leq 76$  dB(A)





PLASTICS AUTOMATION



Master K.  
Master K.

## Single-phase loaders FK KASKO

The proportional valve is designed for the regrind material direct recovery in a closed loop. An easy cleaning of the valve is possible thanks to the special surface finishing. The valve features an integrated control in loader, a direct percentage regulation, and an easy access with quick closing system. Master K is the interface palmtop.

*La valvola proporzionale è utile per il recupero diretto del rimacinato in circuito chiuso. La particolare finitura superficiale permette una facile pulizia della valvola. Il controllo è integrato nell'alimentatore, e la regolazione viene fatta in percentuale diretta, l'accesso alla valvola è pratico e rapido, con chiusura rapida. Master K è il palmtop di interfaccia.*



VP quick closing device detail.  
VP con apertura rapida.

designed by Moretto

Reproduction and/or copying, even partial, are forbidden without written authorization by Moretto S.p.A.

Single - phase loaders		F1K	F3K	F6K	F12K
Hopper capacity	dmc	1	3	6	12
	cft	0.035	0.105	0.211	0.42
Throughput	kg/h	30	50	80	120
	lb/h	66.13	110.23	176.37	264.55



Quick opening hinge.  
Cerniera per apertura rapida.



Discharging valve with gasket detail.  
Particolare della bocca di scarico con guarnizione.



Cover assist opening.  
Apertura assistita del coperchio.



Detail of the integrated control in the container.  
Dettaglio del controllo integrato sul contenitore.